PCT





INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 7:
G09G 3/00, H04N 9/31, G02B 3/06
A1
(11) International Publication Number: WO 00/58932
(43) International Publication Date: 5 October 2000 (05.10.00)
(21) International Application Number: PCT/GB00/01248 (81) Designated States: AE, AL, AM, AT, AU, AZ, BA, BB, BG,

31 March 2000 (31.03.00)

(71) Applicant (for all designated States except US): CAMBRIDGE
3D DISPLAY LTD. [GB/GB]; 26 Faroe Road, London W14

31 March 1999 (31.03.99)

OEP (GB).

(30) Priority Data:

(22) International Filing Date:

9907277.9

12 T

3

(72) Inventors; and
(75) Inventors/Applicants (for US only): TRAVIS, Adrian, Robert,
Leigh [GB/GB]; Wrangaton House, Wrangaton, South Devon TQ10 9HH (GB). MARSTON, Nathan, Stuart [GB/GB];

Christ's College, Cambridge CB2 3BU (GB).

(74) Agent: GIBBS, Christopher, Stephen; Haseltine Lake & Co., Imperial House, 15–19 Kingsway, London, WC2B 6UD (GB).

(81) Designated States: AE, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, IP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

Published

With international search report.

(54) Title: WIDE-FIELD-OF-VIEW PROJECTION DISPLAY

(57) Abstract

ď

L

A wide-field-of-view projection display comprises a circularly symmetric lens (1) and an array of light emitters (2), positioned along the focal circumference of the circularly symmetric lens so that light from each of the light emitters is substantially collimated by the lens in a different direction. A ray-diverting means, such as a slab waveguide (10) or a reflector, ejects the collimated light out of the plane of the lens to the viewer. The planar circularly symmetric lens has no aberration, allowing adjacent views to be seamlessly joined because they can all be diffused by the same angular amount.

